

SEMiX202GB17E4s



SEMiX[®] 2s

SEMiX202GB17E4s

Features


- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- High short circuit capability
- UL recognized, file no. E63532

Typical Applications*

- AC inverter drives
- UPS
- Electronic Welding

Remarks

- Case temperature limited to $T_C=125^{\circ}\text{C}$ max.
- Product reliability results are valid for $T_j=150^{\circ}\text{C}$
- Dynamic values apply to the following combination of resistors:
 $R_{Gon,main} = 1,0/1,9 \Omega$ ($V_{cc}=1200\text{V}/900\text{V}$)
 $R_{Goff,main} = 1,0/1,9 \Omega$ ($V_{cc}=1200\text{V}/900\text{V}$)
 $R_{G,X} = 2,2 \Omega$
 $R_{E,X} = 0,5 \Omega$



GB

Absolute Maximum Ratings				
Symbol	Conditions	Values	Unit	
IGBT				
V_{CES}	$T_j = 25^{\circ}\text{C}$	1700	V	
I_C	$T_j = 175^{\circ}\text{C}$	$T_c = 25^{\circ}\text{C}$	321	A
		$T_c = 80^{\circ}\text{C}$	248	A
I_{Cnom}		200	A	
I_{CRM}	$I_{CRM} = 3 \times I_{Cnom}$	600	A	
V_{GES}		-20 ... 20	V	
t_{psc}	$V_{CC} = 1000\text{ V}$ $V_{GE} \leq 15\text{ V}$ $V_{CES} \leq 1700\text{ V}$	$T_j = 150^{\circ}\text{C}$	10	μs
	T_j			
Inverse diode				
V_{RRM}	$T_j = 25^{\circ}\text{C}$	1700	V	
I_F	$T_j = 175^{\circ}\text{C}$	$T_c = 25^{\circ}\text{C}$	213	A
		$T_c = 80^{\circ}\text{C}$	157	A
I_{Fnom}		200	A	
I_{FRM}	$I_{FRM} = 2 \times I_{Fnom}$	400	A	
I_{FSM}	$t_p = 10\text{ ms, sin } 180^{\circ}, T_j = 25^{\circ}\text{C}$	1170	A	
T_j		-40 ... 175	$^{\circ}\text{C}$	
Module				
$I_{t(RMS)}$		600	A	
T_{stg}		-40 ... 125	$^{\circ}\text{C}$	
V_{isol}	AC sinus 50Hz, t = 1 min	4000	V	

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
IGBT					
$V_{CE(sat)}$	$I_C = 200\text{ A}$ $V_{GE} = 15\text{ V}$ chipllevel	$T_j = 25^{\circ}\text{C}$	1.90	2.20	V
		$T_j = 150^{\circ}\text{C}$	2.30	2.60	V
V_{CE0}	chipllevel	$T_j = 25^{\circ}\text{C}$	0.8	0.9	V
		$T_j = 150^{\circ}\text{C}$	0.7	0.8	V
r_{CE}	$V_{GE} = 15\text{ V}$ chipllevel	$T_j = 25^{\circ}\text{C}$	5.5	6.5	m Ω
		$T_j = 150^{\circ}\text{C}$	8	9	m Ω
$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C = 8\text{ mA}$	5.2	5.8	6.4	V
I_{CES}	$V_{GE} = 0\text{ V}$ $V_{CE} = 1700\text{ V}$	$T_j = 25^{\circ}\text{C}$		2.7	mA
					mA
C_{ies}	$V_{CE} = 25\text{ V}$	$f = 1\text{ MHz}$	18		nF
C_{oes}	$V_{GE} = 0\text{ V}$	$f = 1\text{ MHz}$	0.68		nF
C_{res}		$f = 1\text{ MHz}$	0.58		nF
Q_G	$V_{GE} = -8\text{ V...} + 15\text{ V}$		1600		nC
R_{Gint}	$T_j = 25^{\circ}\text{C}$		3.75		Ω
$t_{d(on)}$	$V_{CC} = 1200\text{ V}$ $I_C = 200\text{ A}$	$T_j = 150^{\circ}\text{C}$	300		ns
t_r	$V_{GE} = +15/-15\text{ V}$	$T_j = 150^{\circ}\text{C}$	38		ns
E_{on}	$R_{Gon} = 2.4\ \Omega$	$T_j = 150^{\circ}\text{C}$	75		mJ
$t_{d(off)}$	$R_{Goff} = 2.4\ \Omega$	$T_j = 150^{\circ}\text{C}$	750		ns
t_f	$di/dt_{on} = 6300\text{ A}/\mu\text{s}$ $di/dt_{off} = 1100\text{ A}/\mu\text{s}$	$T_j = 150^{\circ}\text{C}$	150		ns
E_{off}	$du/dt = 5100\text{ V}/\mu\text{s}$ $L_s = 30\text{ nH}$	$T_j = 150^{\circ}\text{C}$	82		mJ

SEMiX202GB17E4s



SEMiX[®] 2s

SEMiX202GB17E4s

Features

- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- High short circuit capability
- UL recognized, file no. E63532

Typical Applications*

- AC inverter drives
- UPS
- Electronic Welding

Remarks


- Case temperature limited to $T_C=125^\circ\text{C}$ max.
- Product reliability results are valid for $T_j=150^\circ\text{C}$
- Dynamic values apply to the following combination of resistors:
 $R_{Gon,main} = 1,0/1,9 \Omega$ ($V_{cc}=1200\text{V}/900\text{V}$)
 $R_{Goff,main} = 1,0/1,9 \Omega$ ($V_{cc}=1200\text{V}/900\text{V}$)
 $R_{G,X} = 2,2 \Omega$
 $R_{E,X} = 0,5 \Omega$

Characteristics

Symbol	Conditions	min.	typ.	max.	Unit
$t_{d(on)}$	$V_{CC} = 900 \text{ V}$ $I_C = 200 \text{ A}$		360		ns
t_r	$V_{GE} = +15/-15 \text{ V}$ $R_{G on} = 3.3 \Omega$		70		ns
E_{on}	$R_{G off} = 3.3 \Omega$		46		mJ
$t_{d(off)}$	$di/dt_{on} = 3075 \text{ A}/\mu\text{s}$		840		ns
t_f	$di/dt_{off} = 1000 \text{ A}/\mu\text{s}$		170		ns
E_{off}	$du/dt = 4350 \text{ V}/\mu\text{s}$ $L_s = 80 \text{ nH}$		68		mJ
$R_{th(j-c)}$	per IGBT			0.122	K/W

Characteristics

Symbol	Conditions	min.	typ.	max.	Unit
Inverse diode					
$V_F = V_{EC}$	$I_F = 200 \text{ A}$ $V_{GE} = 0 \text{ V}$ chipelevel		2.00	2.40	V
			2.15	2.57	V
V_{F0}	chipelevel	1.16	1.32	1.56	V
			1.08	1.22	V
r_F	chipelevel	2.7	3.4	4.2	m Ω
			5.4	6.8	m Ω
I_{RRM}	$I_F = 200 \text{ A}$		290		A
Q_{rr}	$di/dt_{off} = 5600 \text{ A}/\mu\text{s}$ $V_{GE} = -15 \text{ V}$		73		μC
E_{rr}	$V_R = 1200 \text{ V}$		55		mJ
I_{RRM}	$I_F = 200 \text{ A}$		230		A
Q_{rr}	$di/dt_{off} = 3000 \text{ A}/\mu\text{s}$ $V_{GE} = -15 \text{ V}$		70		μC
E_{rr}	$V_R = 900 \text{ V}$		45		mJ
$R_{th(j-c)}$	per diode			0.276	K/W
Module					
L_{CE}			18		nH
$R_{CC'+EE'}$	res. terminal-chip	$T_C = 25^\circ\text{C}$	0.7		m Ω
		$T_C = 125^\circ\text{C}$	1		m Ω
$R_{th(c-s)}$	per module		0.045		K/W
M_s	to heat sink (M5)	3		5	Nm
M_t	to terminals (M6)	2.5		5	Nm
					Nm
w				250	g
Temperature Sensor					
R_{100}	$T_C=100^\circ\text{C}$ ($R_{25}=5 \text{ k}\Omega$)		$493 \pm 5\%$		Ω
$B_{100/125}$	$R(T)=R_{100}\exp[B_{100/125}(1/T-1/T_{100})]$; $T[\text{K}]$;		$3550 \pm 2\%$		K



GB




Fig. 1: Typ. output characteristic, inclusive R_{CC+EE}




Fig. 2: Rated current vs. temperature $I_C = f(T_C)$




Fig. 3: Typ. turn-on /-off energy = $f(I_C)$




Fig. 4: Typ. turn-on /-off energy = $f(R_G)$




Fig. 5: Typ. transfer characteristic




Fig. 6: Typ. gate charge characteristic




Fig. 7: Typ. switching times vs. I_C




Fig. 8: Typ. switching times vs. gate resistor R_G




Fig. 9: Typ. transient thermal impedance




Fig. 10: Typ. CAL diode forward charact., incl. $R_{CC+EE'}$




Fig. 11: Typ. CAL diode peak reverse recovery current






Fig. 12: Typ. CAL diode recovery charge

SEMiX202GB17E4s

Case: SEMiX 2s



SEMIX 2s



This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX

* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our staff.